Promat PROMASTOP®-IM Grille Technical Data Sheet

General Description


PROMASTOP® IM Grille is an intumescent sealing system for ventilation openings. The expansion of the grill starts at approx. 190°C and seals the opening against spread of smoke and fire.

Field Of Application

PROMASTOP® IM Grille is used as ventilation grill in walls.

System Advantage / Customer Benefit

- Module system
- Slim design
- Resistant to atmospheric influences (light, heat, frost, UV radiation, humidity)



General Technical Properties

Colour	dark grey
Consistency	solid
Dimension (HxWxD)	100x100x60mm
Weight	approx. 220g
Expansion temperature	approx. 190°C
Open cross-sectional area	approx. 70%

Packaging

• 16 pcs./box

Storage Requirements

Store in cool and dry conditions

Safety Instructions

- · Keep out of reach of children
- · Avoid contact with food or beverages
- Please refer to the safety data sheet for additional advice

Promat GmbH

St.-Peter-Straße 25, A-4021 Linz/Austria
Tel: +43 732 6912 0, Fax: +43 732 6912 3740
Email: info@promat.at, www.promat.at

The products must be applied in accordance with regulations for construction material in general and fire stopping in particular, with the applicable national test certificates and approvals and in accordance with applicable national building regulations. Products may only be applied by trained professionals with adequate knowledge and only after thorough review of the installation guidelines, safety data sheets and national test certificates and approvals. All the relevant documents can be obtained free of charge from the web site (see www.Promat.at) or by local dealer. For Non European Union countries separate guidelines are relevant. If required please contact us.

